

PRODUCT DETAILS



634-1261-212P

Heavy Duty Contactor Solenoid Individually Packaged in a Box

Pollak

POP: W

Per Car: 1

CHECK YOUR FIT

[+ Add to Saved List](#)

Installation Instructions

Form No. GF11691.pdf

(<http://eaccess.smpcorp.com/eCatalogs/Downloads/EMD2/GF11691.pdf>)

Part Specifications

Warranty: 1 year

Contact Material: Copper

Electrical Cycle Life: 100,000

Max Duty Cycle: 25%

Max On Time: 6 min

Mounting Bracket Type: Curved Bracket

Operating Temperature: -40°C to 82°C

Voltage: 12 V Intermit. / Pull In Voltage 6 / Hold Voltage 3.5

Amperage Resistive Load Carry 150A/250A / Inductive Load Carry

Rating: 150A/250A / Peak Inductive Inrush 800A

Continuous Duty: No

Coil Resist Ohms: 5.4

Terminal Quantity: 3

Terminal Gender: Male

Terminal Type: Stud

Color/Finish: Black

Hardware included: Yes

Mounting Bracket(s) Included: Yes

Thread Size: (1) grounded 10-32 stud / (2) 5/16-24 Studs

Features & Benefits

Pollak has been providing innovative designs and high-quality parts to the OEM and Aftermarket Heavy Truck, Off-Road, RV, Marine, Industrial, and Towing Industries since 1909.

- Our contactor solenoids are equipped with copper contacts that minimize arcing effects and extend solenoid life, providing enhanced durability.
- We understand and expect the demand for quality, our heavy duty contactor solenoids feature high grade materials for extended service life

- The environmental seal is the centerpiece of the optimized design for higher performance and lower cost
- Our heavy-duty contactor solenoids are designed specifically for electric vehicles and applications requiring tough environmental conditions

For Catalog assistance: (718) 316-4400

[Back to Top](#)
