TAR Ш Ш 6

6

STAR HEADLIGHT & LANTERN CO.

66 Series **Specifications and Features** CRS Technology™

- Long-term reliability
- · Compact, rear-facing speaker with heavy duty
- · Available in a variety of decibel options
- · Industry-standard mounting holes
- · Unique design almost completely protects the speaker from the damage often caused by high-pressure spray, dirt, and fine dust!
- Standard beep: standard single tone, familiar and widely recognized "reverse" tone
- · Improved auto-adjust alarm



66L Series

- Dual Tone "DT": constant emission of sound by switching between two sounds
- Dual Function "DF": alarm has two input wires, each activating a distinct tone, allowing the alarm to be connected to two independent functions
- · Selectable decibel "S": select between two loudness levels by applying voltage to a third wire
- · Auto-adjust "A": automatically adjusts its volume based on the ambient noise
- Dimensions: 4 ³/₁₆"W x 3 ¹/₆"H x 2"D
- Amp draw: 0.3 amps

Model Numbers/Descriptions:

66 Series with wire leads

66-087	10-32V DC, 87 dB, SAE J994, single tone
66-097	10-32V DC, 97 dB, SAE J994, single tone
66-097-12	12V DC only, 97 dB, SAE J994, single tone
66-102	10-32V DC, 102 dB, single tone
66-107	10-32V DC, 107 dB, SAE J994, single tone
66-097DT	12-36V DC, 97 dB, dual tone
66-102DT	10-32V DC only, 102 dB, dual tone
66-707A	10-32V DC, 77-97 dB, auto adjust
66-802A	10-32V DC, 82-102 dB, auto adjust, SAE
	J994 approved
66-807A	10-32V DC, 87-107 dB, auto adjust, SAE
	J994 approved
66-802S	10-32V DC, 87 or 102 dB, selectable
66-907S	10-32V DC, 97 or 107 dB, selectable
66-097DF	10-32V DC, 97 dB, dual function

66L Series with lugs only

66L-087	10-32V DC, 87 dB, SAE J994, single tone
66L-097	10-32V DC, 97 dB, SAE J994, single tone
66L-097-12	12V DC only, 97 dB, SAE J994, single tone
66L-102	10-32V DC, 102 dB, single tone
66L-107	10-32V DC, 107 dB, SAE J994, single tone
66L-097DT	10-32V DC, 97 dB, dual tone
66L-102DT	10-32V DC only, 102 dB, dual tone
66L-707A	10-32V DC, 77-97 dB, auto adjust
66L-802A	10-32V DC, 82-102 dB, auto adjust, SAE J994 approved
66L-807A	10-32V DC, 87-107 dB, auto adjust, SAE J994 approved

Marning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF109 Rev G 01-3-2020





Star Headlight & Lantern Co., Inc. 455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797







6



STAR HEADLIGHT & LANTERN CO.







66L Series

Specifications and Features

- · Rich audible tones combined with familiar sound of a traditional warning alarm
- Narrow array of frequencies
- Individually programmed through a proprietary fixture that incorporates the optimal frequency into • Amp draw: 0.3 amps each alarm
- Emits a composite buzz tone

- Spectrum "SS": Composite of multiple tones, referred to as "multi frequency", tighter frequency range, more universally recognizable warning tone
- Dimensions: $4 \frac{3}{16}$ W x $3 \frac{1}{6}$ H x 2 D

Model Numbers/Descriptions:

66 Series with attached wire leads

66-087SS	10-32V DC, 87 dB, Spectrum™
66-092SS	10-32V DC, 92 dB, Spectrum™
66-097SS	10-32V DC, 97 dB, Spectrum™

66 Series with lugs only

	 	<u> </u>				
66-097SS	10-32\	/ DC.	97	dB,	Spectrum™	

⚠ Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov





Star Headlight & Lantern Co., Inc. 455 Rochester Street Avon, NY 14414 Phone: 585-226-9500





