

## PRODUCT DETAILS

---



# 684-1261-212P

## Heavy Duty Contactor Solenoid Individually Packaged in a Box

**Pollak**

POP: W

Per Car: 1

**CHECK YOUR FIT**

[+ Add to Saved List](#)

---

### Installation Instructions

Form No. GF11665.pdf

(<http://eaccess.smpcorp.com/eCatalogs/Downloads/EMD2/GF11665.pdf>)

**Part Specifications**

Warranty: 1 year

Contact Material: Copper

Electrical Cycle Life: 100,000

Max Duty Cycle: 25%

Max On Time: 6 min

Mounting Bracket Type: Curved Bracket

Operating Temperature: -40°C to 82°C

Voltage: 12 V Intermit. / Pull In Voltage 6 / Hold Voltage 3.5

Amperage Resistive Load Carry 150A/250A / Inductive Load Carry

Rating: 150A/250A / Peak Inductive Inrush 800A

Continuous Duty: No

Coil Resist Ohms: 5.4

Terminal Quantity: 4

Terminal Gender: Male

Terminal Type: Stud

Color/Finish: Black

Hardware included: Yes

Mounting Bracket(s) Included: Yes

Thread Size: (2) 10-32 Studs (non-grounded) / (2) 5/16-24 Studs

---

## Features & Benefits

Pollak has been providing innovative designs and high-quality parts to the OEM and Aftermarket Heavy Truck, Off-Road, RV, Marine, Industrial, and Towing Industries since 1909.

- Our contactor solenoids are equipped with copper contacts that minimize arcing effects and extend solenoid life, providing enhanced durability.
- We understand and expect the demand for quality, our heavy duty contactor solenoids feature high grade materials for extended service life

- The environmental seal is the centerpiece of the optimized design for higher performance and lower cost
- Our heavy-duty contactor solenoids are designed specifically for electric vehicles and applications requiring tough environmental conditions

---

**For Catalog assistance: (718) 316-4400**

**[Back to Top](#)**

---