

FEATURES & BENEFITS

- 12 different selectable flash patterns in either of two phases, plus steady-on
- Extremely low current draw; Circuit board is conformal coated to protect circuitry
- Durable polycarbonate twist on/off lens
- S-Link[™] System* synchronizing capabilities with up to six other units (for hardwire models only). Allows for synchronization with other S-Link compatible products
- Durable, lightweight polycarbonate base, flange 3-hole permanent mount, 1" pipe mount, vacuum magnet mount with cig. plug (on/off and pattern select switch)
- 5 year warranty

PERMANENT MOUNT Voltage: 12 to 24 VDC


Amp Draw: 0.5 amps @ 12 VDC

VACUUM MAGNET

Voltage: 12 VDC

Amp Draw: 0.5 amps @ 12 VDC

APPROVALS: SAE J845 CLASS I ● AMBER ○ WHITE ● RED SAE J845 CLASS II ● BLUE NOT SAE APPROVED ● GREEN



PART#	DESCRIPTION	MOUNT	COLOR		
SHORT LEI	SHORT LENS				
78031	LED Beacon, Class I, Short Lens	Permanent	O White		
78041	LED Beacon, Class I, Short Lens	Vacuum Magnet	○ White		
78033	LED Beacon, Class I, Short Lens	Permanent	Amber		
78043	LED Beacon, Class I, Short Lens	Vacuum Magnet	Amber		
78035	LED Beacon, Class II, Short Lens	Permanent	Blue		
78045	LED Beacon, Class II, Short Lens	Vacuum Magnet	Blue		
78034	LED Beacon, Short Lens	Permanent	Green		
78032	LED Beacon, Class I Short Lens	Permanent	Red		
78030	LED Beacon, Class I Short, Clear Lens	Permanent	Amber		
TALL LENS					
78051	LED Beacon, Class I, Tall Lens	Permanent	O White		
78053	LED Beacon, Class I, Tall Lens	Permanent	Amber		
78055	LED Beacon, Class II, Tall Lens	Permanent	Blue		
78054	LED Beacon, Tall Lens	Permanent	Green		
78052	LED Beacon, Class I, Tall Lens	Permanent	Red		
78050	LED Beacon, Class I, Tall, Clear Lens	Permanent	Amber		

S-Link is a Trademark of Star1889 Headlight & Lantern Co.



FOR MORE INFORMATION VISIT OUR WEBSITE AT GROTE.COM

GROTE'S GOT IT!

*S-LINK TECHNOLOGY: S-Link System is a proprietary technology that will allow similar S-Link products to be synchronized. This would allow for a user to define the flash patterns on multiple devices for a customized, tailored look on a vehicle. Note: Only S-Link compatible products can be synchronized together. Refer to user installation manuals for details on S-Link Synchronization.



230 Travail Rd, Markham, Ontario, Canada L3S 3J1 Tel: 800.268.5612 US: 800.628.0809 www.grote.com

ONNECT & PROTECT



FEATURES & BENEFITS

- 12 different selectable flash patterns in either of two phases, plus steady-on
- Extremely low current draw; Circuit board is conformal coated to protect circuitry
- Durable polycarbonate twist on/off lens
- S-Link[™] System* synchronizing capabilities with up to six other units (for hardwire models only). Allows for synchronization with other S-Link compatible products
- Durable, lightweight polycarbonate base, flange 3-hole permanent mount, 1" pipe mount, vacuum magnet mount with cig. plug (on/off and pattern select switch)
- 5 year warranty

PERMANENT MOUNT Voltage: 12 to 24 VDC


Amp Draw: 0.5 amps @ 12 VDC

VACUUM MAGNET

Voltage: 12 VDC

Amp Draw: 0.5 amps @ 12 VDC

APPROVALS: SAE J845 CLASS I ● AMBER ○ WHITE ● RED SAE J845 CLASS II ● BLUE NOT SAE APPROVED ● GREEN



PART#	DESCRIPTION	MOUNT	COLOR	
SERVICE PARTS				
98221	Replacement Short Lens		○ Clear	
98223	Replacement Short Lens		Amber	
98225	Replacement Short Lens		Blue	
98224	Replacement Short Lens		Green	
98222	Replacement Short Lens		Red	
98171	Replacement Tall Lens		Clear	
98173	Replacement Tall Lens		Amber	
98175	Replacement Tall Lens		Blue	
98174	Replacement Tall Lens		Green	
98172	Replacement Tall Lens		Red	
98470	Branch Guard (Low Profile)			
98460	Branch Guard (High Profile)			



S-Link is a Trademark of Star1889 Headlight & Lantern Co.

FOR MORE INFORMATION VISIT OUR WEBSITE AT GROTE.COM

GROTE'S GOT IT!

*S-LINK TECHNOLOGY: S-Link System is a proprietary technology that will allow similar S-Link products to be synchronized. This would allow for a user to define the flash patterns on multiple devices for a customized, tailored look on a vehicle. Note: Only S-Link compatible products can be synchronized together. Refer to user installation manuals for details on S-Link Synchronization.



230 Travail Rd, Markham, Ontario, Canada L3S 3J1 **Tel**: 800.268.5612 **US**: 800.628.0809

www.grote.com

CONNECT & PROTECT