

CW3200 SERIES DOUBLE ROW

DT04-2P
Female DEU
Mate: DT06-2S



CW3225

CW3214



Youtube.com/Code3Inc

Code 3's double row utility bars offer bright white light output with low amp draw and a relatively low profile. They are available in three lengths with multiple mounting options. These bars are an ideal choice for a variety of applications. Features include 12-24 VDC operation, deutsch connector, powerful five-watt LEDs, flood or combination flood/spot beam patterns, durable aluminum housing and a tough polycarbonate lens.

VOLTS	12-24V
DIMS	3.0" H x 14.0" L x 4.3" D 76mm H x 363mm L x 109mm D (CW3214) 3.0" H x 25.0" L x 4.3" D 76mm H x 635mm L x 109mm D (CW3225) 3.0" H x 33.0" L x 4.3" D 76mm H x 838mm L x 109mm D (ULTY33-DC)

CERTS CE, IP67, IP69K, RoHS

DETAILS

- Deutsch connector
- Built-in vent to prevent fogging
- High-intensity beam
- Adjustable end or extrusion mount
- Aluminum heatsink housing and polycarbonate lens
- Temperature range: -40°F to 158°F (-40°C to 70°C)

MODEL	TYPE	LUMENS (RAW)	AMPS
CW3214	Flood / Spot Combo	2,800	2.7
CW3225	Flood / Spot Combo	4,750	4.3
ULTY33-DC	Flood / Spot Combo	16,800	25.0

