



REVISION HISTORY						
REV.	DESCRIPTION	DATE				
03	REVISED PER EC4751	2020-02-04				
04	REVISED PER EC4751	2020-05-15				
Α	INITIAL RELEASE PER EC4751	2020-06-30				

SPECIFICATIONS

CERTIFICATIONS: UN 38.3

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. RAW LUMENS: 650 lumens
- 3. EFFECTIVE LUMENS: 600 lumens
- 4. ILLUMINANCE (@100 FT): 2.17 lux
- 5. PEAK BEAM INTENSITY: 2019 candela
- 6. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 7. CONNECTION: Battery Powered no power lead
- 8. MOUNTING: MAGNET MOUNT
- 9. HOUSING MATERIAL: ALUMINUM
- 10. LENS MATERIAL: POLYCARBONATE
- 11. PRODUCT WEIGHT: 1.72 LBS (0.77 Kg)

DISCLAIMER

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

NOTES:

- 1. ROHS COMPLIANT
- 2. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

PROPRIETARY AND CONFIDENTIAL INFORMATION

SCALE 1:2			APF	ROVALS	DATE	6	3	_				
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:			DRAWN BY	ABB	2020-05-15				CC	www.eccolin	k.com	
			CHECKED	ABD	2020-05-18	V	X ≺					
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	JLA	2020-05-15	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61 (0)3 63322444						
LIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	SPO	2020-05-19	WORKLAMP,5LED,SQUARE,FLOOD,12VDC						
(. ± 1.0mm (.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	RM	2020-05-19		CUSTOMER PART NO.					
71.00		± 1/64	SALES.	ARS	2020-05-15	N/	<u> </u>					
THIRD ANGLE PROJECTION						SIZE:	Α	DWG.	NO.	EW2461	REV.	
9			Electronically Controlled Use Latest Copy			SHEET	1 OF 1	Project:	EC4751	Date Created: 2020-01-23	1 A	