3 Amber LED 3/4" Clearance Marker and Auxiliary Turn Light by Maxxima, not intended for stand alone use as a front or rear turn signal. Grommet mount, 3 wire leads for connection.

Auxiliary Park Turn Light

Auxiliary Use Only - Must Be Used with Regulation Turn Signal

Polycarbonate Lens and Housing & Sealed Moisture Proof Electronics

Optional Stainless Steel Bezel, Maxxima Part# M50112

5 Year Maxxima Warranty

3 LEDs

Function

FMVSS 108 Standard........ **Yes**

DOT/SAE Spec.................. **J592 J2042**

Functions.......................... **Clearance / Aux turn**

Functions Comments........ **1st Gen had wire splice in-line sausage 1-3/4" x 1/2" x 3/8"**
Red Wire: Auxiliary - Comes with Free Chrome Ring 2023 onward.

Legal Heading................. **P2 P3 PC2**

Origin Product................. **Taiwan**

Dimensions..................... **0.75" dia x 1" high. Hole cutout for grommet: 3/4" dia**
Recommended panel thickness: 0.047" - 0.177"

Specification

No.Leds..............................3.0		Termination.................... **3 ea, 10" with bullet**	
Led Type............................		Connector Supplied......... **no**	
Led Color............................**Amber**		Gasket............................. **No**	
Color Temp.........................**N/A**		Mounting Screws........... **No**	
Beam Pattern......................**N/A**			
		Wire Gauge..................... **22 AWG**	
Voltage (DC)..................... **12.8**		Wire Color...................... **Red / Black / white**	
Amperage Draw.................**70 mA / 35 mA**		Individual Pack................	
Polarity Sensitive.............. **Yes**		Master Pack.................... **200**	
		Shipping Weight.............. **.075**	
Lumens.............................**N/A**		Warning Label.................	
Lens Material.................... **Polycarbonate**		Warranty.......................... **5 Years**	
Maxxshield Coat................ **No**			
Body Material................... **Polycarbonate**		Accessories..................... **M50112, M50133**	
Operating Temp............... **-40 C to + 50 C**			
Ingress Protection (IP)....... **68**			

![Maxxima Product DataSHEET logo]

Black Cable

Black(Side Marker)

Red(Auxiliary Light)

White(GND)

245^{+20}_{-0}

21.0

A — A'

⌀18.6

TOP

15.0

3

A-A'

Old Version