



SS730

FEATURES & BENEFITS

- Wail, Yelp, Air Horn, Phaser, Manual, and Two-Tone
- Self-resetting circuit protection against speaker shorts
- Integrated public address microphone
- Park Kill input
- Auxiliary input
- Replaceable jumpers for option selection
- Positive and negative switching for AUX and PKILL inputs
- High and low voltage shutdown protection
- Drives one or two 100 watt speakers
- Ships complete with positive locking connector, mic clip, mounting bracket, hardware, RFI filter, and instructions
- Trunk mount amplifier
- Output: 100 or 200 watts (1 or 2 speakers)
- Dimensions:
Control head: 2-3/4"H x 6-1/4"W x 1-1/2"D
Amplifier: 2-1/2"H x 7"W x 7-1/3"D
- Voltage: 10-16V DC or 19-32V (-28)
- Frequency: 675-1633Hz
- Amp draw: 8 amps (per speaker)
- Approvals: Exceeds acoustical and environmental requirements, SAE J1849, California Title 13, AMECA listed (when used with StarSignal Speaker drivers and approved tones)

PART	DESCRIPTION
SS730	Full siren with visual LED Diagnostics, 100 or 200 watt, 10-16V DC

Warning: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

SF063 Rev-D 05-11-2023



**FOR MORE INFORMATION
VISIT OUR WEBSITE.
STARSAFETYTECHNOLOGIES.COM**

Star Safety Technologies, LLC
455 Rochester St., Avon, NY 14414
Phone: 585-226-9500 | Fax: 888-478-2797

STAR
Safety Technologies by *Grote*