

GENERAL INFORMATION

The LED Signal Stick alerts traffic in the direction they need to follow. The Signal Stick comes complete with controller (Model No. 11.1000). The controller has an ON/OFF Switch, Rotary Switch and Speed Control Dial. **NOTE:** Shielded wire must be grounded at the Controller. The LED Signal Stick has twelve flash patterns from which to choose:

- 1. Random Flash (Patterns 2-7)
- 2. Quad Flash 2-2
- 3. Quad Flash 4-4
- 4. Double Flash 2-2

INSTALLATION INSTRUCTIONS

- 5. Double Flash 4-4
- 6. Center 2 Outer 2
- 7. Left 4 Right 4
- 8. Center Out

- 9. Right * w/Double Flash
- 10. Right
- 11. Left * w/Double Flash
- 12. Left

Use the L - brackets (included) to mount the 12.6208 light. To install mounting bolts to the signal stick, remove the 4 screws from the end cap and install the mounting bolts into the desired t-slot as shown in drawing. Re-install the end cap.

WIRING INSTRUCTIONS

Black wire to Ground, Red wire to Positive +12V. Yellow wire activates the signal stick in a Random Flash Pattern when +12v is applied. When operating signal stick with controller, All Signal Stick functions will override the Random Flash.

